

BY BARNACLE

EASIEST WAY TO HANG ON DRYWALL!



For best results, be sure to read both sides of these instructions.

THE BEST HANGER FOR DRYWALL!

- ✓ Does not penetrate back of drywall
- ✓ No need to locate studs
- ✔ Pipes, wires and vapor barrier stay safe

WARRANTY AND LIMITATIONS. Barnacle warrants only that the Attach-It product will meet specifications. It is the user's responsibility to insure the drywall is suitable; the object is static, and placed out of the reach of children. Barnacle shall, in no event, be liable for incidental or consequential damages. Barnacle's liability expressed or implied, is limited to the stated selling price of any defective goods.

THE PRODUCTS:



LARGE Attach-Its with screws Holds 50 lbs.

Attach-Its with screws 1 holds 30 lbs.

MEDIUM



SMALL Attach-Its with nails

Holds 10 lbs.



METAL FRAME Attach-Its The Level-It

with screws

Holds 15 lbs.

If you have any questions about Attach-It, please call 800-707-1911. You may also fax 703-935-0253 or e-mail info@attach-lt.com. Visit our website at www.Attach-lt.com for additional product information.

EASY AS 1-2-3

- Great for groupings
- Stays straight

PUT IT ON THE BACK



Small

Attach-It

Mount 2 large Attach-Its or 2 medium Attach-Its using screws provided.





Metal Frame Attach-It

Place the bottom curved portion of the metal frame Attach-It inside the rear channel of regular aluminum frames. Depress sprung side arms down, and push in until only the prongs are outside the frame

GET IT STRAIGHT

Insert top of Level-It between glass and frame






Always mount with prongs pointing

down.

Rest picture on a table or other reference surface and adjust Level-It until bubble is centered.





After pushing picture into wall, remove the Level-It.

PUSH IT IN THE WALL

PLACE HANDS OVER the position of Attach-Its.



PUSH IN and DOWN.



IMPORTANT TIP: Attach-Its work best in pairs. If you only use one it must be mounted at the top and in middle of object.

CAUTION: READ BEFORE USE


ATTACH-ITS ARE MADE FOR DRYWALL.

FULL PENETRATION

To ensure maximum strength, Attach-It prongs must be fully inserted into the drywall. Check that the prongs are all the way into the drywall either visually or by feeling that there is no gap between the wall and the item you have hung.

FLAT WALLS

Bumpy walls can prevent prongs from penetrating fully into the drywall, especially long horizontal pictures hung with small Attach-Its. Before mounting Attach-Its, check that the back of the frame and the wall is flush.



NO PROTRUSIONS

Check that nothing prevents the Attach-Its from full insertion such as old hardware or nails in the walls.

TEXTURED AND FINISHED WALLS

Some drywall has a plaster or skim texture applied for decoration. For thicker textures, large or metal frame Attach-lts are recommended. Remember, Attach-lts must be fully inserted into the drywall in order to function properly.

MOUNT ON SURFACE FLUSH WITH WALL

Mount Attach-Its on the surface of the object that will be in contact with the wall. Imagine Attach-Its work like glue—both surfaces to be glued must cleanly touch each other—it's the same with Attach-Its.





DECORATIVE ITEMS ONLY

Attach-Its are designed to allow you to easily remove and reposition objects. They are designed for decorative (static) objects only. They are not to be used for items that are "in use" such as coat hangers, towel racks, etc. that may be pulled away from the wall.

GLUING ATTACH-ITS

Users report great success gluing Attach-its onto plaster and ceramic objects. It is important to follow the glue manufacturers instructions and leave plenty of time for it to set. Attach-Its will only hold up to the rated strength of the glue. Delicate objects could break if pushed too hard into wall. Consider for suitability. Go to www.Attach-It.com for more information.

SHELVES

- Use large Attach-Its for shelves.
- Small Attach-Its may be used for small sconces.


Do not use Attach-Its on shelves without a support leg.



Leg must be at least as long as the shelf is deep.

Attach-Its mounted on shelves hold less than rated weight.

The longer the leg, the greater weight the shelf will support.



Weight at back of shelf	Best
Evenly centered front to back	
On front edge of shelf	Be careful!

Ensure that the drywall is suitable and that the object(s) placed on the shelf are between the position of the Attach-Its and will be static. To remove shelf, lift up and out of wall. Do not position in reach of children or where shelf may be bumped up and out of the wall.


TIPS

SETS OF PICTURES

Desired finished height of three pictures:



To attain horizontal alignment when hanging groups of pictures, place picture a little above the desired finished height before pushing in and down. 1/16" for the small Attach-It, 1/8" for the large Attach-It, and 3/32" for the metal frame and the medium Attach-It.



NOTE: If you are unsure of your particular application of the Attach-It product, you may wish to try it out first in a closet or other inconspicuous place.

- Q. How does the Attach-It work?
- A. It's really simple. All you do is put the Attach-It on the back of your object, position on wall, and push it in!
- Q. What's the most important thing to remember when using the Attach-It?
- A. Make sure the prongs are pushed all the way into the wall. (To hold the rated weight, prongs must be fully inserted into the drywall.)
- Q. How much weight can Attach-It hold?
- A. Two large Attach-Its hold up to 100 lbs.
 Two medium Attach-Its hold up to 60 lbs.
 Two small Attach-Its hold up to 20 lbs.
 Two metal frame Attach-Its hold up to 30 lbs.
- Q. What kind of walls does the Attach-It work on?
- A. Attach-It is designed for drywall. It does not work on plaster, brick or hard paneling walls. It may work on some soft woods or soft paneling; however, no warranty or representation is made as to the appropriateness of such use.
- Q. How do I know if I have drywall?
- A. Most all homes built from the mid 50's onward have drywall. Additionally, most remodeling in older homes has been done using drywall. To test: push a thumbtack into your wall. If it goes in, you've got drywall.
- Q. Do I have to find a stud?
- A. No. Attach-Its hold without going through the back of the drywall.

 You don't have to look for studs or worry about hitting pipes or
 electrical wires in your walls.

- Q. What if I have a textured surface on my walls?
- A. It depends on how thick the texture is. If the texture is very thin, all Attach-its may work fine. If the texture is thicker, we recommend that you use the large Attach-It. Remember, Attach-Its must be fully inserted into the drywall in order to function properly. Check in an inconspicuous place to see if the Attach-It is suitable.
- Q. Can I use it on antiques?
- A. Yes. Attach-Its are great for any decorative object.
- Q. Will it damage my picture frame?
 - A. No. Only very small nail or screw holes are needed in the back of your frame—the same holes you'd need for the old type of hangers.
- Q. What is the best way to hang a shelf with the Attach-It?
- A. We recommend that you use the large Attach-It. (See above.)

 Please note: the longer the support leg and the more narrow the depth of the shelf, the more weight the Attach-It will support. The Attach-It will support less when the weight is away from the wall. Shelves can support up to 20 lbs.
- Q. Will the metal frame Attach-It work on all metal frames?
- A. The metal frame Attach-It is designed for standard, e.g., Nielsen-Bainbridge and Larson-Juhl, rear channel profile frames.
- Q. Where can I get answers to other questions I may have concerning the best use of Attach-It?
- A Go to our web site at www.attach-it.com, e-mail us at info@Attach-It.com, or call Attach-It Customer Service toll free at 800-707-1911.

